DION UPVC Sheet:

An Unified Solutions for Corrosion, Heat & Sound

Presentation



By: Mr. Alok (Manager – Marketing) Contact: +91 90330 33856 Mail id: marketing@dioninc.in



Understanding Your Needs

Before we get into the specifics, it's important to understand that your procurement decisions likely focus on products that **cost effective**, **non-corrosive**, **durability**, **and long-term value**. DION UPVC Sheets are designed to meet those criteria and more, offering a range of benefits tailored to the roofing needs of your industry.

A. What is DION UPVC Sheet?

- DION UPVC Sheets are **Un plasticized Polyvinyl Chloride (uPVC)** roofing solutions, specifically engineered for **long-lasting performance** in all weather conditions.
- Unlike traditional roofing materials, our uPVC sheets are:
- **3Layer DION UPVC Sheet:** Surface layer- The material is ultra-weather resin, to block the solar ultra violet and reduce the coefficient of heat conductivity, ensure product durability and resistance to chemical corrosion. Surface Intermediate Layer contains Multi foam giving to the material light weight and improved sound and thermal insulating properties. Underlying layer for just a good material toughness special to ensure the strength at the same time, increase the rigidity and light illumination.
- **Rigid and Durable**: Built to withstand extreme weather, UV radiation, and corrosive environments.
- Lightweight but Strong: Easy to handle during installation but tough enough for long-term use.



Company Profile & Our Strength



* DION (An ISO 9001:2015) is a professional largest manufacturer of the uPVC/ASA sheet in India. The Company specializes in the manufacturing and distribution of a wide range of products made from uPVC/ASA material. The company is based in Rajkot, India. Founded in 2011 (A **SAMAY** Group of Company & More than 45years experience in plastic products manufacturing)

* Dion has strong presence in the domestic and global market and supplies uPVC/ASA products to various industries, including Pharma, chemical, fertilizer, iron & metal, Food, hotel, paper. There are 450+ projects clients & 55+ channel networks in all over India.

* As a manufacturer of uPVC sheet to become a largest manufacturer of uPVC & ASA (Anti corrosion sheet) sheet in India and more than 60% market share in this product. With our strength Quality Products, Exceptional customer service, Competitive pricing, Personalization, Convenience, Trustworthiness, Innovation, Social responsibility, Brand reputation & Emotional connection, **Our primary focus and help those industries, where the corrosion issues are a major challenge**.

CORROSION RESISTANCE:

• DION uPVC Sheets can resist the chemical corrosion of acid, alkali, salt etc. for a long time. The test proves that

there is no chemical reaction when dipped in salt, alkali etc.

Page no: 1 of 1

(24hour deep test in the video)

• Ideal use for Chemical, Pharma, Fertilizer, steel & iron industries, coastal areas, chemical processing unit etc.



F-94-95, RUDRAKSHA-II, JASHODANAGAR MEHAMDABAD HIGHWAY, VATVA, AHMEDABAD: 382445, TEL-FAX: 79-25830445, E-Mail: aiekh_plastics@yahoo.com; alekhplastics@gmail.com www.alekhestingcentre.com Doc.No: F/RPT/01

TEST REPORT

No: TR/24-25/0109	Date of issue: 18/05/2024		
Issued to: M/s. Dion Incorporation	Date of receipt: 13/05/2024		
Limda Chowk,	Date of performance of testing: 14/05/24 to 17/05/24		
Rajkot	Sampling details: By customer		
Sample details: UPVC multilayer roo	fing sheet (as stated by the party)		
Sample Packing: Loose Sample c	ondition: Satisfactory Mode of delivery: By courier		
Your reference: Received courier on	13/05/2024 Test condition: 27°C/63% RH		
	Test mould		

lest result				
Sample	Test Property	Unit	Test method	Test value
Sample as above	Thermal resistance	1000	At 70°C/12 hrs	No effect
	Chemical resistance	1000	ASTM D 543	
	a) in dil. HCL			No effect
	b) in dil.NaOH			No effect
	c) in saturated CaCl ₂			No effect

The decision rule applied for statement of conformity, for borderline results, considering the uncertainty of measurment is: NOT APPLICABLE. Opinion & interpretation for this report: NOT APPLICABLE



N.B.: No liabilities are accepted, whatsoever, for this test report. Valid only for the sample tested. Not for publication. Not for legal purpose. END OF REPORT------




R

For Every Season, For Er

AN ISO 9001:2015 Certified Company







FIRE RETARDANT:

• DION uPVC Sheets can Self extinguishing the main body material polyvinyl chloride resin and its chemical performance determine that it is difficult to be burned.



भरत के. एल / BHARATH K. L.

लकनीकी अधिकारी / TECH. OFFICER

CIPET : INSTITUTE OF PETROCHEMICALS TECHNOLOGY (IPT) o of Plastics Engineering & Technology Department of Chemicals & Patrochemicals Winistry of Chemicals & Fertilizets, Gost, of India 0.630, Phase-IV, G. LD, C., Vatva, Ahmedabad-382445 Intel. : (076) 40103600-502, 9223, Fax : (075) 4024360 willigmail.com, ahmestabed@cipet.pov Web. : www.cipet.gov/ Head office : CIPET, Guindy, Chennal - 600 03

2 of 2 कीर्ति जिलेपी / KIRTI TRIVEDI

ारि, माह, खरिकारी / SR, TECH, OFFIC


		PART C	1	Dated : 30.07.2024
		RESULTS		
Sr. No.	Test	Test Method	Unit	Results Obtained
1	Density	ASTM D 792	gm/cc	1.60
2	Vicat Softening Temperature at 10 N	ASTM D 525	°C	79
3	Heat Deflection Temperature at 66 PSI		°C	75.6
4	Heat Deflection Temperature at 264 PSI	ASTM D 648	°C	71.8
5	Heat Deflection Temperature at 1.8MPa		°C	71.8
-	Tensile Strength at break	ASTM D 638	MPa	27.92
6	Elongation at break		%	2,0
7	Flexural Strength	ASTM D 390	N/mm ²	63.48
8	Flammability	UL - 94		Match with Vo
9	Water Absorption (Change in Mass. 24 hrs.)	ASTM D 570	%	0.072
10	Rate of Burning	ASTM D 635		The flame front did not reach the 25mm ref. mark
Ū.	Resistance to Chemical (10% HCL for -24 hrs.)	ASTM D 543	9%	No visible change observed
12	Notch Charpy Impact strength	ASTM D 6110	J/m	105.7
	ARKS : Nil	A RT D e items tested duced in full/part with sissued only for the :	out written	



HEAT & SOUND INSULATION:

• Heat insulation up to 10-15%, The coefficient of heat conductivity is 0.104W/m. °C, which is about 1/3 of clay tile, 1/5 of 10mm thick cement sheet, and 1/2000 of 0.5mm thick color coated sheet. It can be well absorb the noise when influenced by heavy rain, storm and windstorm etc.

AN ISO 9001:2015 Certified Company



Heat & Sound Insulation: The coefficient of heat conductivity is 0.104 W/m. °C, which is about 1/3 of clay tile, 1/5 of 6-mm-thick cement sheet, and 1/2000 of 0.5-mm-thick color-coated steel sheet. It can well absorb the noise when influenced by Strom, and windstorm etc.

Product Features: DION UPVC Sheets



EASY FABRICATION:

• Easy to cut, shape, and install, saving labour time and reducing costs.



www.dioninc.in







Our Products:



DION uPVC SHEET



TRAPEZOIDAL PROFILE



ROUND PROFILE

DION ASA uPVC TILE SHEET



ROYAL TILE SHEET




UPVC PLAIN SHEET

Profile Name	Thickness (mm)	Width (mm)	Standard Length	Color
Trapezoidal Wave Profile	1.5, 2.0, 2.5, 3.0, 3.5, 4.0	1130	8,10,12 Ft.	Blue, White, Green, Gray, Terracotta, Off white, Beige
Round Wave Profile	1.5, 2.0, 2.5, 3.0	1130	8,10,12 Ft.	Blue, White, Green, Gray, Terracotta
ASA uPVC Royal Tile Sheet	2.3, 2.5	1050	2.41,3.07,3.73, 4.38, 5.03, 5.47, 6.13 Mtr.	Gray & Terracotta
ASA uPVC Classic Tile Sheet	2.3, 2.5	1080	2.50,3.0,3.75 Mtr.	Gray & Terracotta

Note: Length can be customized as per customers required on bulk order only.(Trapezoidal wave & round wave profile) Weight (Approx) :- 2.6kg per square meter (1.5mm) 3.4 Kg per square meter (2mm), 4 kg per square meter (2.5 mm), 5.1 kg per square meter (3mm) 5.8 kg per square meter (3.5 mm), 6.3 kg per square meter (4mm)

Purlin span :- 1.5mm < 1.5feet, 2mm < feet, 2.5 mm < 2.5 feet, 3mm < 3 feet, 3.5mm <3.5 feet, 4.0 mm <3.5 feet




R Available Accessories: For Every Season, For Every Reason .. AN ISO 9001:2015 Certified Company ACCESSORIES 3 Way Ridge Main Ridge (1050mm) Main Ridge Cap Fascia Board (1050mm) **Transparent Sheet** RIDGE FOCER SET Wall Flashing Board (1050mm) Side Ridge (1050mm) Side Ridge Cap 4 Way Ridge Tile sheet Plain Ridges (2000mm) UPVC Gutter (8" X 7" X 8") Length – 6Mtr - 3.0mmthickness Gutter Drop outlet **Gutter Joiner Fixer Set** Face curve sheet Gutter drain End cap Air Ventilator Polycarbonate Base Plates End cap FRP GUTTER / CORNER

Applications: Ideal use for Chemical, Pharma, Fertilizer, steel & iron industries, coastal areas, chemical processing unit etc. Due to its **Non corrosive** Properties.

APPLICATIONS


DION is an optimum choice for roofing & cladding in civil and industrial construction as per the efficiency and benefits it provides. It can be used in many applications both exterior and interior. i.e.industrial places, commercial places, residential places & Agricultural firms etc like Factory Building, Warehouses, Market, Vehicle Parking Sheds, Farm House, Water Resorts, Cottages, Chemical Industries, Animal House, Construction House, Schools, Colleges, Hostels, Sheltered Walkways, Security Guard Shelters, roof extensions, summer huts cycles etc.



Note: The white is our raw material color. The other colors are derived from pigmentation and pigment are subject to sunlight fading. Above all information are only for good reference, DION is not responsible for any loss from miss uses or misunderstanding of instruction. Company has power to change in specification at any time. For more details, please visit our website.



• While initial costs may be higher than traditional roofing materials like metal or fiber sheets, DION UPVC Sheets offer a longer lifespan, with minimal maintenance required, leading to significant savings over time. • Energy Savings: The heat insulation reduces cooling costs for buildings by up to 20%, resulting in lower energy bills. • Low Maintenance: The anti-corrosive nature of the material means fewer repairs or replacements, cutting down A. Costlong-term operational expenses. Effectiveness • Long Lifespan: DION UPVC Sheets are built to last 12-15 years, even in harsh environments like coastal areas or industrial sites with exposure to chemicals. • Weather Resistant: These sheets are resistant to UV radiation, meaning they won't fade (white & off white colour), **B. Durability** warp, or crack under prolonaed sun exposure. and Reliability • DION UPVC Sheets meet international standards for roofing materials, including ISO certification for quality and safety. • They are compliant with environmental and building regulations, ensuring smooth project approvals. C. Compliance and Standards



Comparison with Other Roofing Materials:



	Feature	DION UPVC Sheets	Metal Roofing	Fiber Sheets	
	Durability at chemical environment	12-15 years 2-3 years		3-5 years	
	leat Insulation	Excellent	Poor	Moderate	
	Corrosion-Resistant	High	Low	Low	
	Fire Resistance	High	Moderate	Low	
/	Cost Over Time	Low (due to lifespan)	Moderate to High	High	

Unique Selling Proposition (USP):

• **DION UPVC Sheets** outperform traditional roofing materials in all the key areas that matter: durability, energy efficiency, and long-term cost savings.

While other materials degrade, rust, or require frequent maintenance, **DION UPVC Sheets maintain their** strength and appearance for decades

Some of our Valuable Clients:



- ➢ USHA MARTIN LTD. RANCHI (550000 SQ.FT.)
- > SHYAM METALICS FLAT PRODUCTSS PVT. LTD. BAHADURPUR (258000 SQ.FT.)
- ➢ JINDAL STAINLESS LIMITED. JAJPUR (215000 SQ.FT.)
- > INDIAN FARMERS FERTILISERS COOPERATIVE LTD. (IFFCO) PARADEEP, KALOL, SENEGAL (1200000 SQ.FT.)
- SUN PHARMACEUTICAL INDUSTRIES LTD. PANOLI, VADODARA, NAWANSAHAR (2500000 SQ.FT.)
- PIDILITE IND. LTD. VAPI, BOISAR (220000 SQ.FT.)
- > UPL LTD. JHAGADIA, BOISAR (350000 SQ.FT.)
- N R AGARWAL INDUSTRIES LTD. VAPI (85000 SQ.FT.)
- VITAL HEALTH CARE PVT. LTD. VAPI (125000 SQ.FT.)
- ➢ GOOD LUCK INDIA LTD. SECUNDRABAD, SIKARA (450000 SQ.FT.)
- ➢ NIRMA LIMITED. KALATALAV (550000 SQ.FT.)
- > APL APOLLO TUBES LTD. SECUNDRABAD, BHILAI (300000 SQ.FT.)
- ➢ ARADHYA STEEL PVT LTD. DAVANGERE (125000 SQ.FT.)
- HINDUSTAN COCA COLA BEVERAGES PRIVATE LIMITED. MYSORE (62000 SQ.FT.)
- DR.REDDY'S LABORATORIES LTD. VISAKHAPATNAM (127000 SQ.FT.)

*Note: The mentioned quantities are approximate, and supply is ongoing.



Durability of DION uPVC Sheet:



BENEFITS OF DION UPVC MULTILAYER SHEET

Save 4 times replacement and new sheet installations cost of metalic sheet · T/cs apply

Replacement of Metal Sheet:





PROJECT TYPE: GALVANIZING PLANT COVER AREA: 180000 SQ.FT. (APPROX.) ISSUE TYPE: HIGHLY CORROSION METAL SHEET LIFE: MAX. 2 YEARS REPLACE MATERIAL: DION UPVC SHEET THICKNESS: 3.5MM MAX. LENGTH: 39 FEET. LIFE EXPECTATION: 5 CYCLES OF METAL SHEET WITH PROPER INSTALLATION GUIDELINES.

Replacement of Asbestos Sheet:





Industry Type: Fertilizer & Chemical Current project Coverage area: 65000 square feet approx. Old used sheet type: Asbestos Sheet Replaced sheet type: **DION UPVC Sheet** 3.0mm thickness Issue type: Brittleness & dusting due to chemical enviornment.



























































1/11/11











Conclusion

DION UPVC Sheets offer unmatched value in terms of Anti corrosion, cost-efficiency, durability, and performance. We are committed to providing a **long-term partnership** that goes beyond just selling a product – we offer ongoing support and ensure that your roofing solutions are robust, sustainable, and cost-effective.

Thank You for your Valuable Time



DION INCORPORATION

Corporate Office : 403, Alap A, Limda Chowk, Rajkot - 360001, Gujarat (India) Contact : +91 281 2460580, +91 90330 57756 E mail : marketing@dioninc.in Web : www.dioninc.in Factory : Plot No 345 to 348 & 367 to 370, Golden Green Industrial Park, Ravki Road Village: Khambha, Ta. : Lodhika, Rajkot - 360311, Gujarat (India) Contact : +91 90330 33656 E mail : info@dioninc.in Web : www.dioninc.in

DION Quality & Aesthetics - A perfect Combination to match your Roofing needs.